



CE Marking SECURGLASS
UNI EN 14449:2005
*Laminated glass and laminated safety glass for use in
building and construction*
DECLARATION OF PERFORMANCE no. 168



Certificate number: N/A
Certifying body: N/A

Nova Vetro S.r.l.

Registered Office: via F. Ferranti, 35 - Industrial Zone Taccoli - 62027 San Severino Marche (MC)

Production Sites: via F. Ferranti, 35 - Industrial Zone Taccoli - 62027 San Severino Marche (MC)
via F. Bruni, 35 - Industrial Zone Taccoli - 62027 San Severino Marche (MC)

Tel.: 0733.64371 - **Fax:** 0733.645104 - **email:** novavetro@novavetro.it - **www.novavetro.it**

Nova Vetro S.r.l., assuming full responsibility, affirms the following features of the CE mark for the product **SECURGLASS** di specified below: laminated glass and laminated safety glass for use in building and construction according to standard **UNI EN 14449:2005**.

| | Securglass 55.2 (float 5 mm / pvb 0,76 mm / float 5 mm) | AVCP System | Performance |
|----|---|--------------------|--------------------|
| 1 | Resistance to fire (EN 13501-2) | 1 | NPD |
| 2 | Reaction to fire (EN 13501-1) | 3,4 | NPD |
| 3 | External fire performances | 3,4 | NPD |
| 4 | Bullet resistance (EN 1063) | 1 | NPD |
| 5 | Explosion resistance (EN 13541) | 1 | NPD |
| 6 | Burglar resistance (EN 356) | 3 | NPD |
| 7 | Pendulum body impact resistance (EN 12600) | 3 | 1 (B) 1 |
| 8 | Resistance against sudden temperature change and temperature differentials | 4 | NPD |
| 9 | Wind, snow, permanent and imposed load resistance | 4 | NPD |
| 10 | Direct airborne sound reduction (EN 12758): Rw (C;Ctr) | 3 | NPD |
| 11 | U-value (EN 673) Normal emissivity en coated side (EN 12898) | 3 | 5.5 0,89 |
| 12 | Light transmission/reflection (EN 410): tv / rv / r'v | 3 | 87 / 8 |
| 13 | Solar transmission/reflection/factor (EN 410): te / re / r'e Solar factor: g | 3 | 69 / 7 / 75 |
| 14 | Durability | 3 | conforme |

NPD = No Performance Determined

San Severino Marche
November 28, 2014

The Chief Executive Officer
(Lucentini Samuele)