



**CE Marking SECURGLASS**  
**UNI EN 14449:2005**  
*Laminated glass and laminated safety glass for use in  
building and construction*  
**DECLARATION OF PERFORMANCE no. 298**



**Certificate number:** N/A  
**Certifying body:** N/A

**Nova Vetro S.r.l.**

**Registered Office:** via F. Ferranti, 35 - Industrial Zone Taccoli - 62027 San Severino Marche (MC)

**Production Sites:** via F. Ferranti, 35 - Industrial Zone Taccoli - 62027 San Severino Marche (MC)  
via F. Bruni, 35 - Industrial Zone Taccoli - 62027 San Severino Marche (MC)

**Tel.:** 0733.64371 - **Fax:** 0733.645104 - **email:** novavetro@novavetro.it - **www.novavetro.it**

**Nova Vetro S.r.l.**, assuming full responsibility, affirms the following features of the CE mark for the product **SECURGLASS** di specified below: laminated glass and laminated safety glass for use in building and construction according to standard **UNI EN 14449:2005**.

	<b>Securglass 18/19 R</b> ( float 5 mm / pvb 0,76 mm / float 8 mm / pvb 0,76 mm / float 5 mm )	<b>AVCP System</b>	<b>Performance</b>
1	Resistance to fire (EN 13501-2)	1	NPD
2	Reaction to fire (EN 13501-1)	3,4	NPD
3	External fire performances	3,4	NPD
4	Bullet resistance (EN 1063)	1	NPD
5	Explosion resistance (EN 13541)	1	NPD
6	Burglar resistance (EN 356)	3	P4A / P6B
7	Pendulum body impact resistance (EN 12600)	3	1 (B) 1
8	Resistance against sudden temperature change and temperature differentials	4	NPD
9	Wind, snow, permanent and imposed load resistance	4	NPD
10	Direct airborne sound reduction (EN 12758): Rw (C;Ctr)	3	NPD
11	U-value (EN 673) Normal emissivity en coated side (EN 12898)	3	5.1 0,89
12	Light transmission/reflection (EN 410): tv / rv / r'v	3	83 / 8
13	Solar transmission/reflection/factor (EN 410): te / re / r'e Solar factor: g	3	59 / 6 / 67
14	Durability	3	conforme

NPD = No Performance Determined

San Severino Marche  
November 28, 2014

**The Chief Executive Officer**  
( Lucentini Samuele)