

**CE Marking SECURGLASS****UNI EN 14449:2005***Laminated glass and laminated safety glass for use in building and construction***DECLARATION OF PERFORMANCE no. 15**

Certificate number: N/A

Certifying body: N/A

Nova Vetro S.r.l.**Registered Office:** via F. Ferranti, 35 - Industrial Zone Taccoli - 62027 San Severino Marche (MC)**Production Sites:** via F. Ferranti, 35 - Industrial Zone Taccoli - 62027 San Severino Marche (MC)

via F. Bruni, 35 - Industrial Zone Taccoli - 62027 San Severino Marche (MC)

Tel.: 0733.64371 - **Fax:** 0733.645104 - **email:** novavetro@novavetro.it - **www.novavetro.it**

Nova Vetro S.r.l., assuming full responsibility, affirms the following features of the CE mark for the product **SECURGLASS** di specified below: laminated glass and laminated safety glass for use in building and construction according to standard **UNI EN 14449:2005**.

	Securglass 666.4 (float 6 mm / pvb 0,76 mm / float 6 mm / pvb 0,76 mm / float 6 mm)	AVCP System	Performance
1	Resistance to fire (EN 13501-2)	1	NPD
2	Reaction to fire (EN 13501-1)	3,4	NPD
3	External fire performances	3,4	NPD
4	Bullet resistance (EN 1063)	1	NPD
5	Explosion resistance (EN 13541)	1	NPD
6	Burglar resistance (EN 356)	3	P4A
7	Pendulum body impact resistance (EN 12600)	3	1 (B) 1
8	Resistance against sudden temperature change and temperature differentials	4	NPD
9	Wind, snow, permanent and imposed load resistance	4	NPD
10	Direct airborne sound reduction (EN 12758): Rw (C;Ctr)	3	NPD
11	U-value (EN 673) Normal emissivity en coated side (EN 12898)	3	5.1 0,89
12	Light transmission/reflection (EN 410): tv / rv / r'v	3	83 / 8
13	Solar transmission/reflection/factor (EN 410): te / re / r'e Solar factor: g	3	59 / 6 / 67
14	Durability	3	conforme

NPD = No Performance Determined

San Severino Marche
November 28, 2014**The Chief Executive Officer**

(Lucentini Samuele)